

# VMVF125 "FLOW SQUARE" Ø125 shockproof polystyrene valve

---

## VMVF125 "FLOW SQUARE" Ø125 shockproof polystyrene valve

---




---

### FEATURES

---

The white plastic ventilation valve model "FLOW SQUARE" Ø125 is intended for intake and extraction air in residential and commercial buildings. It is specially designed to be installed on the ceiling or wall.

Made entirely of shockproof polystyrene, it can be mounted directly on the Ø125 pipe or associated with the Ø125 VMAVC\_AP adapter .

---

### TECHNICAL DATA

---

| Code    | Air flow rate<br>m <sup>3</sup> /h | Values                         |                             |                                  |
|---------|------------------------------------|--------------------------------|-----------------------------|----------------------------------|
|         |                                    | Pressure drop $\Delta P$<br>Pa | Crossing speed $V_k$<br>m/s | Sound power level $L_w$<br>dB(A) |
| VMVF125 | 45                                 | 3                              | 2,6                         | 22                               |
|         | 60                                 | 5                              | 3,3                         | 22                               |
|         | 75                                 | 8                              | 4,2                         | 23                               |
|         | 90                                 | 12                             | 5,2                         | 27                               |
|         | 120                                | 21                             | 6,8                         | 34                               |
|         | 150                                | 34                             | 8,6                         | 40                               |

---

### DIMENSIONS

---

| Code    | ØD (mm) | A (mm) | B (mm) | C (mm) |
|---------|---------|--------|--------|--------|
| VMVF125 | 118     | 185    | 29     | 30     |

